



Zala 150, 180 Extra

bench with backrest

Instructions

ID: 63333, 63335 EAN: 8591792633337, 8591792633351

e-sportshop.cz

Package contents

Part number / description

- 1. wooden lath, 9 pieces, of which 2 with one rounded edge
- 2. Metal side panel, 2 pieces
- 3. Metal connecting rod, 2 pieces
- 4. Metal plate-seat reinforcement, length 34 cm, 1 piece (only at the Zala Extra 150 bench)
- 5. Metal plate-backrest reinforcement, length 25 cm, 1 piece (only at the Zala Extra 150 bench)
- 6 L-shaped metal reinforcement for seat and backrest (only at the Zala Extra 180 bench)
- 7. Self-tapping wood screw long, length 3 cm, 18 pieces
- 8. Self-tapping wood screw short, length 2.4 cm,
- 9 pieces (Zala Extra 150), 11 pieces (Zala Extra 180)
- 9. Connecting screw with thread, length 3 cm, 4 pieces
- 10. Metal expansion anchor bolt, 4 pieces





Assembly instructions

- 1. Place the metal sides 2 on the floor next to each other about the length of the wooden slats.
- 2. Place the two connecting rods 3 in the inner part of one side part and lightly screw with screw 9 do not tighten. Then place it on the other side and fasten with screw 9, do not tighten.
- 3. Insert five wooden slats 1 of the seat into the lower part of the sides with the painted side up. Place the bar with the rounded edge first.
- 4. Screw the slats to the sides with long self-tapping screws. 7 Always point the hole in the side to the center of the slats beforehand.
- 5. Insert four wooden slats 1 for backrest part into the upper part of the side panels with the painted side facing upwards thread the slats at an angle and slide them into the side panels. Lastly, place the bar with the rounded edge.
- 6. Screw the slats to the sides with long self-tapping screws. 7. Always point the hole in the side to the center of the slats beforehand.
- 7. Tighten the screws 9 to the connecting rods 3.
- 8. Turn the assembled bench upside down and, for the Zala Extra 150 bench, screw the metal reinforcement 4 to the center of the seating surface with short self-tapping screws 8 in turn, and screw the metal reinforcement 5 to the center of the backrest part.
- 9. For the Zala Extra 180 bench, attach L-shaped reinforcement 6 to the center of the seat and support surface and screw it to the backrest with short self-tapping screws 8. If you want to fix the bench to a solid surface, use the fix bolts 10 and attach them to the cut-outs in the legs of the bench.



Importer to Czech Republic:

RADANSPORT s.r.o.

Za Otýlií 10 370 01 České Budějovice email: obchod@e-sportshop.cz phone: +420 387 411 543